


ES1520

No-Cut Electric Strike



FEATURES:

- Designed for use with Cylindrical Locksets
- for Hollow Metal Frame Applications
- **No frame cutting is required** - Special ramp design allows the latchbolt to exit from an unmodified frame
- Non-Handed, Fully Reversible
- Field Reversible for Fail Safe or Fail Secure Operation
- Static Strength: 1500 lbs (680 kg)
- Dynamic Strength: 70 ft-lbs
- Endurance Rating: 250,000 Cycles (UL Tested),
1,000,000 Cycles (Factory Tested),
Exceeds Grade 1 Standards)



*Special Keeper Ramp Design
for Quick and Easy Installation*

SPECIFICATIONS:

- Voltage: Dual 12/24VDC
- Current Draw: 300mA @ 12VDC, 150mA @ 24VDC
- Latch Throw: $\frac{9}{16}$ " (15mm)
- Keeper Width: $1 \frac{7}{16}$ " (36mm)
- Mount: Mortise
- Body Construction: Zinc Alloy

PACKAGING INCLUDES:

- 1 Stainless Steel Faceplate
- Stick-On Template for easier installation

PATENTS, APPROVALS, AND LISTINGS:

- UL1034 Burglary-Resistant Listed: BP21351
- UL294 Access Control System Listed: BP21351

