

# FES1665

**(Fire Rated)**  
No-Cut Electric Strike



**FEATURES:**

- Designed for use with Cylindrical Locksets
- for Hollow Metal Frame Applications
- **No frame cutting is required** - Special ramp design allows the latchbolt to exit from an unmodified frame
- Non-Handed, Fully Reversible
- Field Reversible for Fail Safe or Fail Secure Operation
- Static Strength: 1500 lbs (680 kg)
- Dynamic Strength: 70 ft-lbs
- Endurance Rating: 250,000 Cycles (UL Tested), 1,000,000 Cycles (Factory Tested, Exceeds Grade 1 Standards)
- Optional Latch Monitor **FES1665-M**, indicates when door is latched. (Consult factory for availability)



Special Keeper Ramp Design for Quick and Easy Installation

**SPECIFICATIONS:**

- Voltage: Dual 12/24VDC
- Current Draw: 300mA @ 12VDC, 150mA @ 24VDC
- Latch Throw: 3/4" (19mm)
- Keeper Width: 1 7/16" (36mm)
- Mount: Mortise
- Body Construction: Stainless Steel

**PACKAGING INCLUDES:**

- 1 Stainless Steel Faceplate
- Stick-On Template for easier installation

**PATENTS, APPROVALS, AND LISTINGS:**

- UL1034 Burglary-Resistant Listed: BP21351
- UL294 Access Control System Listed: BP21351
- UL10B, UL10C, NFPA252, CAN/ULCS104 (3hrs) Fire Rated - **ETL Listed**: Control No. 5028159

Note: FES1665 Series Electric Strike is fire rated in Fail Secure operation only. Using it in Fail Safe operation negates the fire rating.

