

# DELAYED EGRESS MAGLOCK KIT

UL LISTED ALL-IN-ONE KIT WITH MAGLOCK, SOUNDER AND KEYSWITCH



## PRIMARY APPLICATIONS



## DESCRIPTION

BEA's Delayed Egress Maglock Kit is a user friendly security solution for out-swinging perimeter doors. The kit meets a variety of building, fire and life safety codes.

A 1200 lb, pressure-sensing maglock is coupled with a keyswitch and sounder to create an easy-to-install solution that controls and monitors door access.

The keyswitch can be positioned in a convenient location to create authorized personnel access points.

Note: Not intended for outdoor environments

## FEATURES & BENEFITS

- Double door (2 single doors) can be synchronized
- Authorized egress time programmable 0 – 15 seconds
- Selectable 30 second door prop alarm
- LED color and flashes can be customized
- Monitored fire alarm input
- Delayed Egress can be triggered with pressure on the door or with a REX input (or disabled completely)
- UL 294 listed



BEA, Inc.  
RIDC Park West  
100 Enterprise Drive  
Pittsburgh, PA 15275-1213

Customer Service: 800.523.2462  
Technical Support: 800.407.4545  
[www.BEAinc.com](http://www.BEAinc.com)


## TECHNICAL SPECIFICATIONS

|                                      |                                                                                                                    |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Housing Dimensions</b>            | 10.8125 in (W) x 2.875 in (H) x 2.125 in (D)                                                                       |
| <b>Armature Dimensions</b>           | 7.4375 in (W) x 2.375 in (H) x 0.625 in (D)                                                                        |
| <b>Voltage / Tolerance</b>           | 12 – 24 VDC; $\pm 10\%$                                                                                            |
| <b>Max. Power / Current Draw</b>     |                                                                                                                    |
| Maglock & Sounder                    | 0.49 A / 12 VDC<br>0.24 A / 24 VDC                                                                                 |
| Low Voltage Supply Detection / Alarm | < 8 V                                                                                                              |
| <b>Holding Force</b>                 | Up to 1200 lb                                                                                                      |
| <b>Mortise Cylinder</b>              | 1.125 in cylinder with straight cam required,<br>NOT INCLUDED<br><br>Requires Part<br>10CYLINDERKA or 10CYLINDERKD |
| <b>Operating Temperature</b>         | 14 °F – 140 °F                                                                                                     |
| <b>Norm Conformance</b>              | UL / CUR Listed FWAX<br>Special locking arrangements                                                               |
| <b>Compliance Provisions</b>         | IBC, SBC, UBC, BOCA, or NBC of Canada, NFPA 101                                                                    |


## RELATED PRODUCTS



**10MAGDE1**  
DELAYED EGRESS  
MAGLOCK KIT



**10CYLINDERKA**  
MORTISE CYLINDER,  
KEYED ALIKE



**10CYLINDERKD**  
MORTISE CYLINDER,  
KEYED DIFFERENT



**10KEYPADU**  
UNIVERSAL  
KEYPAD



**10KEYPADUSL**  
UNIVERSAL SLIM-LINE  
KEYPAD



**10PS12-24**  
110-1224 VAC  
POWER SUPPLY

